

Thermo Scientific Orion Star A325

Premium pH/conductivity portable meter

The Thermo Scientific™ Orion™ Star A325 pH/Conductivity Portable Meter is the top choice for testing samples anywhere. It is rugged and dependable, making it ideal for every sample, every day, everywhere.



The Thermo Scientific Orion Star A325 pH/Conductivity Portable Meter is the top choice for advanced measurements on location. Get the information you need quickly and easily from the large, backlit graphic LCD display. Informative display shows one or both pH and conductivity channels with temperature. Additional helpful information includes electrode status, time, date, sample ID, user ID and calibration information.

Features and Benefits

- Easy meter operation assured with on-screen text prompts, menu-specific function keys and a multi-language interface
- Don't miss a reading—AUTO-READ™ locks in the stable reading on your screen, ready indicator alerts when readings are stable and timed reading gathers data in specific time intervals
- Up to 5 point pH calibration with automatic recognition for USA/NIST and DIN buffers or manual option for custom buffer values
- Automatic or manual conductivity calibration
- Auto-ranging measurements for high accuracy across all conductivity ranges
- Selectable reference temperatures of 5, 10, 15, 20 or 25 °C with linear, non-linear or EP curve options for temperature compensated conductivity readings
- Non-volatile memory holds up to 5000 data points with time and date stamp
- Easily transfer data with the USB and RS232 ports and complimentary Orion Star Com computer software
- Four AA batteries (included) provide over 800 hours of operation or purchase the universal power adapter (sold separately)
- Perfectly portable, IP67-rated waterproof and protected to take anywhere
- 3 year meter replacement warranty



Thermo
SCIENTIFIC

Thermo Scientific Orion Star A325 pH/Conductivity Portable Meter

| Specifications | |
|---------------------|---|
| pH | Range: -2.000 to 20.000 Resolution: 0.1, 0.01, 0.001 Relative Accuracy: ±0.002 Calibration Points: Up to 5 Calibration Editing: Yes |
| mV/RmV | Range: ±2000.0 mV Relative Accuracy: ±0.2 mV or ±0.05 % of reading whichever is greater E_H ORP Mode: Yes |
| Conductivity | Range: 0.001 µS to 3000 mS Resolution: 0.001 µS minimum, auto ranging, up to 4 significant digits Relative Accuracy: 0.5 % of reading ±1 digit > 3 µS, 0.5 % of reading ±0.01 µS ≤ 3 µS Reference Temp.: 5, 10, 15, 20, 25 °C Temperature Compensation: Linear, nonlinear nLFn & nLFu, EP (USP), off Compatible Cell Constants: 0.001 to 199.9 Calibration Points: Up to 5 points Calibration Editing: Yes |
| Resistivity | Range: 2 ohm to 100 meg-ohm Resolution: 1 ohm or 0.1 meg-ohm, auto ranging Relative Accuracy: 0.5 % reading ±1 digit |
| Salinity | Type: Practical salinity or natural sea water Range: 0.06 to 80.00 psu, 0.05 to 42.00 ppt Relative Accuracy: 0.5 % reading ±1 digit |
| TDS | Range: 0.001 to 200.0 ppt Relative Accuracy: ±0.5 % reading ±1 digit TDS Factor Range: Linear 0.02 to 9.99 |
| Temperature | Range: -5 to 105 °C, 23 to 221 °F Resolution: 0.1 °C, 0.1 °F Relative Accuracy: ±0.1 °C, ±0.1 °F Offset Calibration: 1 point |
| Datalogging | Memory: 5000 with time and date stamp Log Function: Manual, ready (includes AUTO-READ), timed |
| Inputs | pH Electrode: BNC, reference pin Conductivity or ATC Probe: 8-pin mini-DIN |
| Output | RS232, USB |
| Power | AC Adapter: Optional—universal, 100-240 VAC Battery Power: Included—4 AAs Battery Life: 800 hrs |



thermoscientific.com/water

© 2013 Thermo Fisher Scientific Inc. All rights reserved. Certified System StandardsMark logo is a trademark of SAI Global. All other trademarks are the property of Thermo Fisher Scientific Inc. & its subsidiaries

Water Analysis Instruments

North America
Toll Free: 1-800-225-1480
Tel: 1-978-232-6000
info.water@thermo.com

Netherlands
Tel: (31) 020-4936270
info.water.uk@thermo.com

China
Tel: (86) 21-68654588
wai.asia@thermofisher.com

India
Tel: (91) 22-4157-8800
wai.asia@thermofisher.com

Singapore
Tel: (65) 6778-6876
wai.asia@thermofisher.com

Meter Ordering Information

| Part No. | Description |
|------------------|--|
| STARA3250 | Orion Star A325 pH/Conductivity Portable Meter - Four AA batteries (installed) - Printed quick start guide and literature CD - USB computer cable |
| STARA3255 | Orion Star A325 pH/Conductivity Portable Meter Kit - 8107UWMMMD Orion Ultra Triode gel-filled epoxy-body pH/ATC electrode, 3 m cable - 013010MD Orion DuraProbe conductivity probe, 3 m cable - 910410-WA Orion pH 4.01 buffer pouches - 910710 Orion pH 7.00 buffer pouches - 911010 Orion pH 10.01 buffer pouches - 810001 Orion ROSS electrode storage solution, 475 mL - 01100710 Orion 1413 µS conductivity std pouches - 911110 Orion rinse solution pouches - Protective armor with electrode holders and storage sleeve - Hard-sided field case - Four AA batteries (installed) - Printed quick start guide and literature CD - USB computer cable |

Accessories Ordering Information

| Part No. | Description |
|-------------------|--|
| STARA-CS | Orion Star A series portable meter hard-sided field case |
| STARA-AR | Orion Star A series portable meter armor with pH electrode holder, conductivity and DO probe holder, stand and adjustable hand-strap |
| STARA-ESPH | Orion pH electrode holder for portable Star A series meter armor |
| 810017 | Orion pH electrode storage sleeve for pH electrode holder |
| STARA-ESCD | Orion conductivity and DO probe holder for portable Star A series meter armor |
| 8107UWMMMD | Orion ROSS Ultra Triode |
| 013010MD | Orion DuraProbe conductivity probe |
| 1010003 | Universal power adapter, 100-240 V, 50/60 Hz |
| 910410-WA | Orion pH 4.01 buffer pouches, 10 pack |
| 910710 | Orion pH 7.00 buffer pouches, 10 pack |
| 911010 | Orion pH 10.01 buffer pouches, 10 pack |
| 911110 | Orion pH rinse solution pouches, 10 pack |
| 011008 | Orion 100 µS conductivity std, 5 x 60 mL |
| 01100710 | Orion 1413 µS conductivity std, 10 pack |
| 01100610 | Orion 12.9 mS conductivity std, 10 pack |
| 1010001 | Orion conductivity calibration resistor kit |

For more information, contact your local Thermo Scientific products dealer or call our customer and technical service experts at 1-800-225-1480 (for the US and Canada) or visit www.thermoscientific.com/water.



STARA-CS



STARA-AR



Japan
Tel: (81) 045-453-9175
wai.asia@thermofisher.com

Australia
Tel: (613) 9757-4300
In Australia (1300) 735-295
InfoWaterAU@thermofisher.com